# **Accella Polyurethane Systems Safety Data Sheet**

24-Hr. Emergency Phone Number:

# 1. Identification of Substance:

Product Name: Foamsulate 1000

Telephone: Supplier Identification: 770-607-0755

Accella Polyurethane Systems

Address: 100 Enterprise Drive Cartersville, GA 30120

CHEMTREC (800) 424-9300

Product Use: Polyurethane polyol component

# 2. <u>Hazards Identification</u>:

## **GHS Ratings:**

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Organ toxin single exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance) - Human evidence in exceptional cases
Organ toxin repeated exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases

## **GHS Hazards**

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H371	May cause damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

## **GHS Precautions**

P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER in case of overexposure.
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment is urgent (see Section 4 First Aid measures)
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse

SDS for: Foamsulate 1000 Page 1 of 6 P302+P352 IF ON SKIN: Wash with soap and water

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P309+P311 IF exposed or you feel unwell: Call a POISON CENTER or doctor/physician

P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with Section 13

#### Signal Word: Danger



## 3. Composition/Data on Components:

Chemical Name	CAS number	Weight Concentration %
Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis [[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol	940912-28-7	10.00% - 20.00%
2-Propanol, 1-chloro-, phosphate (3:1)	13674-84-5	5.00% - 10.00%
Diethylene glycol	111-46-6	5.00% - 10.00%
Amine Catalyst	33329-35-0	1.00% - 5.00%
2-(Dimethylamino)ethanol	108-01-0	0.10% - 1.00%

#### 4. First Aid Measures:

physician

Inhalation: If inhaled and symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

**After Eye Contact:** Rinse opened eye for at least 15 minutes under running water. Remove contact lenses if present and easy to do so, and continue rinsing. If irritation persists contact

After Skin Contact: Clean affected area with soap and plenty of water.

After Swallowing: Consult physician.

Notes to Physician: Treat symptomatically

## 5. Fire Fighting Measures:

Flash Point: >200°F, 93°C

LEL: N/A UEL: N/A

Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical

Information about Protection against Explosions and Fires: Closed containers may

rupture when exposed to extreme heat.

SDS for: Foamsulate 1000 Page 2 of 6

**Dangerous Products of Decomposition:** Oxides of carbon, oxides of nitrogen, hydrocarbons, oxides of phosphorus, hydrocarbons, traces of HCN.

**Protective Equipment:** Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

# 6. Accidental Release Measures:

Person-Related Safety Precautions: Avoid contact with skin and eyes.

**Measures for Environmental Protection:** Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

## 7. Handling and Storage:

Information for Safe Handling: Avoid contact with skin or inhalation.

**Storage Requirements:** Store in dry, well ventilated area. Keep containers tightly closed. Store between 60°F-100°F. Material may settle.

# 8. Exposure Controls and Personal Protection:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl) amino]methyl]-4-branched nonylphenol 940912-28-7	Not Established	Not Established	Not Established
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	Not Established	Not Established	Not Established
Diethylene glycol 111-46-6	Not Established	Not Established	Not Established
Amine Catalyst 33329-35-0	Not Established	Not Established	Not Established
2-(Dimethylamino)ethanol 108-01-0	Not Established	Not Established	Not Established

Engineering Controls: No specific measures required.

**General Protective and Hygienic Measures:** Usual precautionary measures should be adhered to when handling chemicals.

Respiratory protection: None required if work area is propertly ventilated.

Hand Protection: Protective chemical resistant gloves.

Eye Protection: Safety glasses.

SDS for: Foamsulate 1000 Page 3 of 6

Body Protection: Protective work clothing. Launder separately.

## 9. Physical and Chemical Properties:

Appearance: Off white liquid

Vapor Pressure: N/A
Vapor Density: N/A
Specific Gravity 1.10
Freezing point: N/A

Boiling range: 285 - 342°C

Evaporation rate: N/A
Explosive Limits: N/A

Autoignition temperature: 229°C

Odor: Mild

Odor threshold: N/A

pH: N/A

Melting point: N/A

Solubility: N/A

Flash point: >200°F, 93°C

Flammability: N/A
Partition coefficient (n- N/A
octanol/water):

Decomposition temperature: N/A

## 10. Stability and Reactivity:

Chemical Incompatible Materials: Avoid contact with isocyanates and strong oxidizing agents.

Hazardous Polymerization: Not expected to occur.

**Dangerous Products of Decomposition:** Oxides of carbon, oxides of nitrogen, hydrocarbons, oxides of phosphorus, hydrocarbons, traces of HCN.

## 11. Toxicological Information:

#### **Mixture Toxicity**

Oral Toxicity LD50: 2,917mg/kg Inhalation Toxicity LC50: 28mg/L

#### **Component Toxicity**

13674-84-5 2-Propanol, 1-chloro-, phosphate (3:1)

Oral LD50: 500 mg/kg (Rat) Dermal LD50: 1,230 mg/kg (Rabbit) Inhalation LC50: 5 mg/L (Rat)

33329-35-0 Amine Catalyst

Dermal LD50: 1,150 mg/kg (Rabbit) Inhalation LC50: 2 mg/L (Rat)

108-01-0 2-(Dimethylamino)ethanol

Oral LD50: 1,803 mg/kg (Rat) Dermal LD50: 1,220 mg/kg (Rabbit) Inhalation LC50: 1,641 ppm (R

#### **Toxicity Values Listed if Known**

**Acute Toxicity:** 

Eyes: Irritating to eyes

Skin: Harmful in contact with skin

**Inhalation:** Not expected to be a route of exposure **Ingestion:** Harmful if swallowed. Consult physician

Chronic Effects: Possible harmful target organ effects

Routes of Entry: Ingestion, skin contact, eye contact

Target Organs: Eyes, Skin, Digestive tract

SDS for: Foamsulate 1000 Page 4 of 6

#### Chemicals with Known or Possible Carcinogenic Effects:

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

## 12. Ecological Information:

**General Information:** Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13. Individual component ecotoxicity listed if known.

#### **Component Ecotoxicity**

2-Propanol, 1-chloro-, phosphate 96 Hr LC50 Brachydanio rerio: 56.2 mg/L [static]; 96 Hr LC50 Pimephales

(3:1) promelas: 98 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30 mg/L [static]

48 Hr EC50 Daphnia magna: 63 mg/L

72 Hr EC50 Desmodesmus subspicatus: 45 mg/L; 96 Hr EC50

Pseudokirchneriella subcapitata: 4 mg/L

Diethylene glycol 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through]

48 Hr EC50 Daphnia magna: 84000 mg/L

Amine Catalyst 48 Hr LC50 Orzyias latipes 430 mg/L

48 Hr EC50 Daphnia 48 mg.L

2-(Dimethylamino)ethanol 96 Hr LC50 Pimephales promelas: 81 mg/L [static]

48 Hr EC50 Daphnia magna: 98.77 mg/L

72 Hr EC50 Desmodesmus subspicatus: 35 mg/L

## 13. Disposal Considerations:

**Recommendation:** Observe local requirements. Dispose of in accordance with local/state/federal regulations.

## 14. Transport Information:

Not considered a dangerous good according to transport regulations unless specifically cited below:

Agency Proper Shipping Name UN Number Packing Group Hazard Class

## 15. Regulatory Information:

**OSHA HAZARD COMMUNICATION STANDARD:** This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard.

#### **California Proposition 65**

#### (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

## **Massachusetts Right To Know List:**

2-(Dimethylamino)ethanol 108-01-0 0.1 to 1.0 %

2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5  $\,$  5 to 10  $\,\%$ 

## **New Jersey Right To Know List:**

2-(Dimethylamino)ethanol 108-01-0 0.1 to 1.0 %

SDS for: Foamsulate 1000 Page 5 of 6

## Pennsylvania Right To Know List:

2-(Dimethylamino)ethanol 108-01-0 0.1 to 1.0 % Diethylene glycol 111-46-6 5 to 10 % 2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5 5 to 10 %

#### All Substances Listed on TSCA Inventory Unless Noted:

- None

## 16. Other Information:

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Accella Polyurethane Systems. The data on these sheets relates only to the specific material designated herein. Accella Polyurethane Systems assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 3/15/17 Reviewer Revision 2

Date Prepared: 2/20/2017

SDS for: Foamsulate 1000 Page 6 of 6

Printed: 3/15/17 at 4:58:13PM