

GLOBE KLEEN | 2002™

Viscous Resin Remover, Isocyanates & Polyurethane Foam Cleaner

GLOBE KLEEN | 2002™ Viscous Resin Remover, Isocyanates & Polyurethane Foam Cleaner

- Low VOC
- non-Flammable
- non-HAPs
- Non-Corrosive
- No ODC's
- Water miscible
- Recyclable
- non-Ozone Depleting

Environmentally Sensible, **VISCOUS** Resin Remover, Isocyanates & Polyurethane Foam cleaner.

It is a mixture of organic solvents, wetting agents and a corrosion inhibitor designed to replace Chlorinated Solvents, Acetone, MEK, Methylene Chloride and Caustic Based Cleaners. Due to its low vapor pressure and high boiling point It evaporates 237 times slower than Acetone and MEK and 600 times slower than Methylene Chloride. This means, whatever quantity you purchase, you will use.

Compatible and non corrosive on various substrates such as; metal, plastic and glass.

It easily adheres to vertical and horizontal substrates and effectively removes cured urethane foam deposits and build-up from mixing heads, troughs, conveyor parts, side walls, floors, rollers, foam cutting devices and molds.

- ~ Polyurethane Foam (Reacted Part A & B), Flexible & Rigid Polyurethane Foam, both MDI and TDI Esters and Ethers, Cured Polyurethane Reactive Hot Melt Urethane Adhesives from roll coating equipment & dispensing equipment, as well as, many other Industrial Adhesives.
- ~ Polyols, Crystallized Isocyanates, and other urethane intermediates.

Application

Use **Full Strength (do not add water)** at **Room Temperature by BRUSH or ROLLER**. Once soils are dissolved, scrape off soils. Parts can be wiped with a damp cloth. **Use Natural Rubber Gloves when handling this product. Do not Heat or Atomize this product.**

Typical Properties

Appearance:	Viscous Clear Liquid - Colorless to slight amber
Flash Point:	> 169 °F Pensky-Martins
Odor:	Mild
Surface Tension (dynes/cm 24) (water = 1.0):	24
pH (10% solution in water @ 68 °F):	6.2 - 6.6
Viscosity (Centipoise @ 68 °F): (Brookfield)	4000-5000
Ideal Operating	Full Strength
Ideal Operating Temp (°F):	Room Temperature
Specific Gravity:	0.9835 - 0.9924 (@ 68 °F)
Weight/Gal.	8.40- 8.45 (lbs. /gal.)
Component Boiling Point:	356 - 396 @ 760 mm Hg (°F)
Component Vapor Pressure:	0.20 - 0.90 mm Hg
VOC Content (ASTM D-2369, Method 24)	3.85 lbs./gal or 437 grams/liter
Recycling Parameters (Vacuum Distillation)	300 °F and 27 mm Hg Pressure
Product #	02-W209570



RECOMMENDED MATERIALS TO USE FOR; O-Rings, Gaskets, Hoses And Pump Packaging

- * FEP-Teflon
- * Ethylene-Propylene Copolymer
- * Ryton
- * Butyl Rubber
- * Kalrez
- * Buna-S
- * Fluorosilicone Rubber
- * Melamine
- * Mild Steel
- * Nylon 101
- * Halar

MATERIALS TO AVOID

- * Viton
- * Phenolic Polyester
- * Noryl EN-265
- * ABS
- * Polyurethane
- * Noryl -731
- * Durel
- * PVC
- * Polysulfone
- * Kynar
- * Buna-N
- * Ultem
- * Lucite
- * Hypalon
- * Valox
- * PET
- * Lexan

Safety & Handling Precautions

Refer to Safety Data Sheet prior to use, disposal & additional safe handling.

Direct contact of **GLOBE KLEEN | 2002™ Viscous Resin Remover, Isocyanates & Polyurethane Foam Cleaner**, will cause a serious eye irritation or skin irritation, It is important to utilize recommended gloves (natural rubber), safety goggles and other suitable protective clothing your company recommends. Aspiration hazard if swallowed. Keep liquid and vapor away from heat, sparks and flames. Keep container closed. Use with adequate ventilation. DO NOT take internally. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling.

Disposal

Refer to Safety Data Sheet prior to use, disposal & additional safe handling.

Even though **GLOBE KLEEN | 2002™ Viscous Resin Remover, Isocyanates & Polyurethane Foam Cleaner** has a low order of toxicity, * with a low risk of environmental harm. Effluent analysis is required for proper waste disposal. **Discharge your distill bottom and screened out solids according to Federal, State and Local Regulations.**

HMIS Rating: Health = 2 Fire = 2 Reactivity = 0

Packaging & Storage

HDPE UN Rated

1 Gallon Jugs, 5 Gallon Pails & 55 Gallon Steel Drums (closed cap)

GO GREEN™ Saturated Wipes

90 (12" x 12") Pre Moistened Wipes in an Easy Carry Bucket (NON - Viscous)

Store this product in its original container in a dry area above freezing and less than 100 °F.

Global Specialty Products - USA, Inc.

10 Eagle Avenue, Suite 500 - Mount Holly, New Jersey 08060-1649
Phone: 609-518-7577 Fax: 609-518-5277 www.gsp-usa-inc.com

04162018