

● COMPRESSOR INSTALLATION



Compressor Station

1. Screw compressor
2. Air Receiver
3. Electronic drain
4. Condensate separator filter
5. Coalescent pre-filter
6. Schulz dryer
7. Coalescent post filter
8. Activated carbon filter (absorption)

COMPACT COMPRESSOR LINE



Highly Efficient Compact Models

The COMPACT line of Schulz Rotary Screw air compressors offers superior performance in a compact package. Featuring a tank mounted solution, these compressors present an efficient design which integrates technology and performance for any application.



SRP 3008



SRP 3015



SRP 3025



SRP 3040

Model	Code	Motor		Maximum Pressure		Discharge Connection	Free Air @125psi		ASME Tank	Noise Level	Net Weight	Width x Height x Depth
		hp	Kw	bar	psig		cfm	l/min				
SRP 3008 COMPACT	970.3891-0	7,5	5,5	8,6	125	1/2"	25	722	60 / horiz	83	422	35 x 42 x 18
SRP 3015 COMPACT-II	970.3454-0/F	15	11	8,6	125	3/4"	51	1.444	60 / horiz	86	430	53 x 55 x 24
SRP 3025 COMPACT	970.2840-0	25	18	8,6	125	3/4"	89	2.510	80 / horiz	86	630	61 x 60 x 26
SRP 3040 COMPACT	970.3233-0	40	30	8,6	125	1"	150	4.247	120 / horiz	91	980	64 x 71 x 30